

# Configuration - Global

Workflows Import **Configuration** Notifications Audit Log Advanced Configuration

Screen Location: [Confluence Administration](#) Workflows section Configuration

## Overview

This screen is used to set Global configuration options.

## Configuration

**Configuration**  
Configuration for workflow User Interface and Task behaviour.

Edit

  

**Workflow Activity and Drafts Visibility**

Default Tasks Mode **Lenient**

State's Task Behaviour **If the page state changes, open tasks will be moved to new state**

Default Approval Workflow **Simple approval workflow**

Approval Comment **Optional**  
Require comment on Approval or Rejections.

Page Update Reset Approval **Reset**

Published View Macro Transform **Enabled**  
Changes the include and excerpt-include macros to render the workflow approved version of the referenced page.

Send Usage Statistics

**Space Administrators and Page Editors**

Note: Some of these settings can be overridden at Space Level, on a space-by-space basis – see: [Configuration - Space Tools](#)

Setting	Options	Notes
<p><b>Workflow Activity and Drafts Visibility</b></p> <p>Who can see workflow activity and unpublished drafts?</p> <p>See also:</p> <ul style="list-style-type: none"> <li><a href="#">Publishing</a></li> <li><a href="#">Status Indicator Circles</a></li> </ul>	<p><b>Space Administrators and Page Editors</b></p>	<p><b>Recommended for most use cases.</b></p> <p>Unpublished drafts and activity reports will not be visible to users who would otherwise normally be able to view the content.</p>
	<p><b>Anybody</b></p>	<p>Anyone who could normally view the content will be able to view drafts and activity reports. They will also be able to take part in <a href="#">Content reviews</a> (v4.6+).</p>
<p><b>Default Tasks Mode</b></p> <p>Who can complete tasks?</p> <p>See also:</p> <ul style="list-style-type: none"> <li><a href="#">Tasks</a></li> </ul>	<p><b>Strict</b></p>	<p>Only the task assignee or task creator.</p>
	<p><b>Lenient</b></p>	<p><b>Recommended for most use cases.</b></p> <p>Any user who can edit the page/blog.</p>
<p><b>State's Task Behaviour</b></p> <p>What happens to incomplete tasks from the current state if the workflow transitions to a new state?</p>	<p><b>If the page state changes, open tasks will be closed</b></p>	<p>Incomplete tasks will be closed.</p>

See also: <ul style="list-style-type: none"> <li><a href="#">Tasks</a></li> </ul>	<b>If the page state changes, open tasks will be moved to new state</b>	<b>Recommended for most use cases.</b>  Incomplete tasks will be copied to the new workflow state.
<b>Default Approval Workflow</b>	<i>List of workflows</i>	This option has been removed from versions 5+. <i>Prior to version 5, when clicking the workflows button on a page without a workflow, there was an option to add an "approval", which added whatever global workflow set as the default approval workflow to the page.</i>
<b>Approval Comment</b>  Mandate reviewer comment when Approving or Rejecting content?  See also: <ul style="list-style-type: none"> <li><a href="#">Reviews</a></li> </ul>	<b>Optional</b>	<b>Recommended for most use cases.</b>  Comment is optional.
	<b>Required</b>	A comment must be added during content reviews.
<b>Page Update Reset Approval</b>  If an approval (content review) is in progress, what effect does editing the content have?  See also: <ul style="list-style-type: none"> <li><a href="#">Reviews</a></li> </ul>	<b>Reset</b>	Any existing Approve/Reject decisions will be reset.
	<b>Ignore</b>	Existing Approve/Reject decisions will be retained.
<b>Published View Macro Transform</b>  Which version of content should the { <a href="#">include</a> } and { <a href="#">excerpt-include</a> } macros show?  See also: <ul style="list-style-type: none"> <li><a href="#">Same-space publishing</a></li> </ul>	<b>Enabled</b>	<b>Recommended in most use cases.</b>  Use published version if available, otherwise use latest version regardless of workflow state.
	<b>Disabled</b>	Show latest version, regardless of workflow state.
<b>User Onboarding</b>	<b>Checkbox</b>	When enabled introductory information and tips will be shown to new users: <a href="#">User Onboarding</a>
<b>Send Usage Statistics</b>	<b>Checkbox</b>	When enabled, anonymous usage statistics will be sent to Comalatech to help improve the product.

## Security

### Security

Configure in which spaces page workflows can be defined. Spaces are indicated as a comma separated list of space keys. You can also define what users can import workflows.



Space Workflows **can be defined in any space**

Page Workflows **can be defined in any space**

Workflow Importer Group **confluence-users**

(Only members of this group can import workflows into spaces)

Email Any Address **Disabled**

Allow the send email workflow macro to send to any email address, if disabled it will only be able to send emails to registered users.

Setting	Options	Notes
---------	---------	-------

<p><b>Space Workflows</b></p> <p>Which spaces can use <a href="#">Space Mode</a>?</p>	<p><i>List of spacekey</i></p>	<p>A list of comma-separated space keys</p> <p>Leave empty for no spaces, or specify <code>ANY</code> to indicate all spaces</p>
<p><b>Page Workflows</b></p> <p>Which spaces can use <a href="#">Page Mode</a>?</p>	<p><i>List of spacekey</i></p>	<p>A list of comma-separated space keys</p> <p>Leave empty for no spaces, or specify <code>ANY</code> to indicate all spaces</p>
<p><b>Workflow Importer Group</b></p> <p>Space admins in the specified group are allowed to import workflows.</p> <p>See also:</p> <ul style="list-style-type: none"> <li>• <a href="#">Import - Global</a></li> <li>• <a href="#">Import - Space Tools</a></li> <li>• <a href="#">Workflows Exchange</a></li> </ul>	<p><i>User group</i></p>	<p>Set as confluence-users to allow all space admins to import workflows.</p> <p>Note: After a workflow is imported, it can be used just like any other workflow; the restriction only applies to the action of importing, not subsequent use.</p> <p><b>⚠</b> Make sure you enter a valid user group name.</p>
<p><b>Email Any Address</b></p> <p>Which email addresses can be used in the <code>{send-email}</code> macro?</p> <p>See also:</p> <ul style="list-style-type: none"> <li>• <a href="#">Notifications - Global</a></li> <li>• <a href="#">Notifications - Space Tools</a></li> </ul>	<p><b>Disabled</b></p>	<p><b>Recommended in most use cases.</b></p> <p>Only email addresses associated with a registered user account</p>
	<p><b>Enable</b></p>	<p>Any email address can be used</p>

## Loop Watchdog

These settings are used to detect infinite loops and terminate any offending workflows. It's recommended to leave the default values.

### Loop Watchdog

Configure the parameters for the loop detection watchdog. The workflow engine will disable the workflow after the maximum events is reached in the given threshold time on a page by a single user.



Maximum Events **20**

Time Threshold (seconds) **20**

Likely causes of infinite loops include:

- cyclic or recursive use of the `{set-state}` macro
- cyclic use of the `duedate` parameter on the `{state}` macro.

Setting	Options	Notes
<p><b>Maximum Events</b></p> <p>If this amount of events is exceeded on a single page by a single user, the threshold timer will start (see below).</p>	<p><i>Number</i></p>	<p>Default: 20</p>
<p><b>Time Threshold (seconds)</b></p> <p>If Maximum Events is exceeded for this amount of time, it will be treated as an infinite loop and the process will be terminatd.</p>	<p><i>Number</i></p>	<p>Default: 20</p>