

# reject-children macro

[Where to use it?](#) | [Parameters](#) | [Events](#) | [Example](#) | [All examples](#) | [See also](#)

## Overview

The `{reject-children}` macro can be used to reject a specific approval, where active, on all child pages of the page where the action was triggered.

## Where to use it?

Optional.

One or more `{reject-children}` macros can be put in a [{trigger} macro](#).

## Parameters

Parameter	Required	Default	Notes
<i>unnamed first parameter</i>	✓		Name of the approval to reject. Only applies to child pages where there is an active approval of that name.
<code>comment</code>			Rejection comment: <ul style="list-style-type: none"><li>• Plain text</li><li>• Can use any character set supported by your Confluence server – except some <a href="#">reserved characters</a>.</li></ul>

## Events

The following [Events](#) are associated with rejections:

- `newsrejected`
- `pagerejected`

## Example

```
{workflow:name=Reject Children}
  {state:Editing|submit=Content Review}
  {state}
  {state:Content Review|approved=Published|rejected=Editing}
    {approval:Review}
  {state}
  {state:Published}
  {state}
  {trigger:trigger:pagerejected|approval=Review}
    {reject-children:Review|comment=Parent approval rejected}
  {trigger}
{workflow}
```

## All examples

### Content by label

There is no content with the specified labels



## See also

[Workflow Authoring Guide:](#)

- [Reviews](#)
- [States](#)
- [Transitions](#)
- [Events](#)
- [Triggers](#)

- [Actions](#)

Reporting Guide:

- [Workflow Report Macro - Approvals](#)