

pagefooter macro

[Where to use it?](#) | [Parameters](#) | [Example](#) | [All examples](#) | [See also](#)

Overview

The `{pagefooter}` macro renders its body content (wiki markup) in the context of the page or blog post that your workflow is applied to.


Note: This macro is an alternative to the `footer` (or `footertemplate`) parameter of the `{workflow}` macro.

Where to use it?

Optional.

One `{pagefooter}` can be put in a `{workflow}` macro.

Parameters

Parameter	Required	Default	Notes	Ver
<i>macro body</i>	✔		Footer content: <ul style="list-style-type: none">• Wiki markup – see Confluence Wiki Markup• Can use any character set supported by your Confluence server – except some reserved characters. The following macros can be used in the footer: <ul style="list-style-type: none">• get-metadata macro• pageactivity macro• pagestatus macro• workflowreport macro	3.1+
<i>visibility</i>		contributors	Who can see the footer? <ul style="list-style-type: none">• contributors – users who can edit the page• readonly – users who can view, but not edit, the page• all – both contributors and readonly users <h3>Content by label</h3> <p>There is no content with the specified labels</p> 	3.1+

Example

```
{workflow:name=Page Footer}
  {pagefooter}
    wiki markup to show at bottom of page
  {pagefooter}
  {state:Example}
  {state}
{workflow}
```

All examples

Content by label

There is no content with the specified labels

See also

[Workflow Authoring Guide:](#)

- [Notifications](#)



- [Events](#)
- [Triggers](#)
- [Actions](#)

Reporting Guide:

- [Workflow Macros](#)
- [Confluence Macros](#)